Scraper Light 55w-80w-110w



Ideals GB can now offer an extensive range, made to order, of IP67 rated focused lighting. Unlike traditional LED Floodlights which whilst very bright, have a wide beam angle, therefore they do not throw any light a great distance. This has been overcome with the introduction of the Scraper Lights. These units use top quality Cree LED Chips and a 3.5 Degree Optic Beam arrangement. Call now for more information.

pecification	_
Product Code	
Dimension(mm)	
.ED Quantity	
.ED Power	
Rated Power	
Cool White Light Cast Distance	
Warm White Light Cast Distance	e
RGB Light Cast Distance	
Color	

sv	V-24/24*2W-55W
L38	0xW145xH153mm
	24pcs
	24*2W
	55W
Max.1	18m@4800Lm@50lux
Max.9	94m@4500Lm@50lux
ľ	Max.59m@50lux
sin	gle color/DMX RGB



Specification
Product Code
Dimension(mm)
LED Quantity
LED Power
Rated Power
Cool White Light Cast Distance
Warm White Light Cast Distance
RGB Light Cast Distance
Color

SW-36/36*2W-80W	/
L538xW145xH153mr	m
36pcs	
36*2W	
80W	
Max145m@7200Lm@5	Olux
Max116m@6800Lm@5	Olux
Max.72m@50lux	
single color/DMX RG	В



Spec	cification
Proc	luct Code
Dim	ension(mm)
LED	Quantity
LED	Power
Rate	d Power
Cool	White Light Cast Distance
War	m White Light Cast Distance
RGB	Light Cast Distance

	SW-48/48*2W-110W
-	.660xW145xH153mm
	48pcs
	48*2W
	110W
Ma	x166m@9600Lm@50lux
Ma	x132m@9120Lm@50lux
	Max83m@50lux

1	

Material	
LED Chip	
Color	
Input Voltage	
Control mode	
Beam Angle	
Lifetime	
Protection Grade	
working temp.	

extr	ruded aluminium+tempered glass	
	Cree	
	single color/DMX RGB	
	AC110V/AC220-240V/DC24V	
	DMX512	
	3.5°	
	50,000H	
	IP67	
	-35°C-+55°C	

Ideals (GB) Limited Unit 3 Brookside Centre Sumpters Way Southend SS2 5RR Tel: 01702 460855 Fax: 01702 460655

email: sales@idealsgb.co.uk web: www.idealsgb.co.uk