


## FFMLS Superior Ribbon Technical Information

Forward Facing Superior Standard Output LED Ribbon is used for general mood and feature lighting where the highest light output & Quality is essential, whilst still conforming to environmental requirements and energy efficiency. Available in a huge range of colours and colour temperatures. All ribbon is available in bespoke lengths to meet exact project requirements.



Wattage Per Metre	14.4
IP Rating	20 - 67
Maximum Single Length	5m
Chip Variety	2835
Voltage	DC24V
LED Brand	Samsung
CRI	>90
Colours Available	Warm White 2900-3100k Natural White 3900-4100k Cool White 5900-6100k Colours - Please enquire
RGB Available	No
Cut Points	Every 100mm / 6 LEDs
LEDs Per Metre	60
Lumens Output Per Metre	1100 (Based on White)
Lumens Per Watt	76.4
Dimensions	10mm (W) x 3mm (H)
Beam Angle	Greater than 120 degrees
Lamp Life	50,000 + Hours
Fixing	3M Tape

### Dimming



24v Dimmer  
with or without  
Remote



1-10v Module  
Use with 1-10v  
System



DMX Module  
Use with DMX  
System



Bluetooth  
WiFi  
Wireless



240v Mains  
Dimmable  
Drivers

Ideals (GB) Limited  
Unit 3 Brookside Centre  
Sumpters Way  
Southend  
SS2 5RR

Tel: 01702 460855  
Fax: 01702 460655

email: [sales@idealsgb.co.uk](mailto:sales@idealsgb.co.uk)  
web: [www.idealsgb.co.uk](http://www.idealsgb.co.uk)