

FFXLS-Mini Superior Ribbon Technical Information

Forward Facing Superior Output Mini LED Ribbon is used for general mood and feature lighting where the smallest dimensions are paramount, whilst still conforming to environmental requirements and energy efficiency. Available in a huge range of colours and colour temperatures. All ribbon is available in bespoke lengths to meet exact project requirements.



Wattage Per Metre	9.6
IP Rating	20 - 67
Maximum Single Length	5m
Chip Variety	3528
LED Brand	Samsung
CRI	>90
Colours Available	Extra Warm White 2400-2600k Warm White 2900-3100k Natural White 3900-4100k Cool White 5900-6100k Colours - Please enquire
RGB Available	No
Cut Points	Every 50mm / 6 LEDs
LEDs Per Metre	120
Lumens Output Per Metre	1050 (Based on White)
Lumens Per Watt	109.4
Dimensions	5mm (W) x 3mm (H)
Beam Angle	Greater than 120 degrees
Lamp Life	50,000 + Hours
Fixing	3M Tape

Dimming



24v Dimmer
with or without
Remote



1-10v Module
Use with 1-10v
System



DMX Module
Use with DMX
System



Bluetooth
WiFi
Wireless



240v Mains
Dimmable
Drivers

Ideals (GB) Limited
Unit 3 Brookside Centre
Sumpters Way
Southend
SS2 5RR

Tel: 01702 460855
Fax: 01702 460655

email: sales@idealsgb.co.uk
web: www.idealsgb.co.uk